

# IC-756PROII HF TRANSCEIVER

**TX Frequencies:** 160-10M; 6M  
**RX Frequencies:** .030-60.0 MHz  
**Receiver System:** Triple conversion  
**Modes:** USB, LSB, CW, RTTY, AM, FM  
**Power Output:** SSB, CW, RTTY, FM 5-100W; AM 5-40W  
**DSP Type:** IF 32 bit floating point DSP  
**Channels:** 101  
**Additional Features:** Realtime spectrum scope  
 Dual watch  
 5 inch color TFT display  
 Digital IF filter with 51 passband widths  
 121 microphone equalized audio settings  
 Multiple DSP controlled AGC loops  
 CW memory keyer  
 Triple band stacking register  
 Optional voice synthesizer  
 Separate RX antenna  
 Transverter I/O  
 Selectable digital filter shape CW & SSB  
 Improved noise reduction control  
 New Noise blanker level control  
 Low floor noise level in band scope

**Includes:** Radio  
 Microphone (HM-36)  
 DC Power Cable (OPC-025D)  
 CW Key Plug  
 Owners Manual

**Box Weight:** 26 lbs per radio  
**Number in Case:** 2



**\*Warranty: 1 Year**

MODEL	DESCRIPTION
IC-756PRO2 22	HF Transceiver